

**Dual-Port.**

**blink**

## Series 7 Plus

High Powered Level 2 EV Charging

With its compact form factor, ease of installation, commercial-grade aluminum body, and ENERGY STAR certification, the Series 7 Plus charging station is the perfect charger for your electrified fleet.

### POWERFUL • DUAL-PORT • COMPACT

#### Series 7 Plus Benefits

- Configurable up to 80A Max per port
- Dual-port design for two vehicles to charge simultaneously
- Easy-to-read back-lit LCD screen
- Universal J1772 plug compatible with all-electric and plug-in hybrid electric vehicles\*
- Bright station status LED indicator lights
- Data communication via built-in 4G LTE
- Robust remote management tool via Blink Fleet portal and Blink Network\*\*
- Remote station management
- Flexible access control and pricing
- Rugged aluminum enclosure
- Pedestal and wall-mount options



**Electronic Office**  
S Y S T E M S

NEW IDEAS. NEW SOLUTIONS.

[www.electronicofficesystems.com](http://www.electronicofficesystems.com) PH: (973) 808-0100

330 Fairfield Road Fairfield, NJ 07004

\*Tesla adapter required

\*Actual charging speeds may vary based on environmental and other factors and are not guaranteed

\*\*Coming soon

The product image shown is for illustration purposes only and may not be an exact representation of the product.

# Series 7 Plus Technical Specifications



<b>ELECTRICAL SPECIFICATION AC OUTPUT</b>		<b>80 A</b>
Number of Ports	Two	
Current	Configurable up to 80A Max per port	
Power	Up to 19.2kW (@240VAC) or 16.64kW (@208VAC) Max per port	
Energy Metering Accuracy	+/- 1%	
Charging Connector	SAE J1772	
<b>ELECTRICAL SPECIFICATION – AC INPUT</b>		
Input Connector	Hardwired	
Voltage	208 or 240 VAC	
Service Panel Breaker	Two-pole common trip 100A breaker, dedicated circuit per port	
Power Connection	Line 1, Line 2 and GND (no neutral) per port	
Standby Power	3.46 W Typical	
<b>SAFETY SPECIFICATION</b>		
Safety, Ground Fault Circuit Interrupt	20ma CCID with auto retry (every 15 seconds)	
Automatic Plug-Out Detection	Power terminated per SAE J1772 spec	
Surge Protection	6kV @3,000a	
<b>NETWORK SPECIFICATION</b>		
Data Communication	Cellular 4G LTE	
Charging Infrastructure Communication	OCPP 1.6 compliant	
Remote Management	Remote access, diagnostics, Over-The-Air (OTA) software update enabled	
Load Management	Smart, dynamic allocation and distribution of power to each port	
<b>USER INTERACTION SPECIFICATION</b>		
Charging Status Indicator	High visibility, multi-color LED visual status indication	
Display	LCD Screen - 4 lines, 20 characters per line	
Authentication	RFID: ISO14443 Type A & B, MiFare, Felica, ISO15693	
<b>ENVIRONMENTAL SPECIFICATION</b>		
Enclosure	Aluminum, NEMA 3R certified	
Operating Humidity	Up to 95% non-condensing	
Operating Temperature	-30 degree C to +50 degree C ambient	
Operating Altitude	≤6560 ft	
<b>MECHANICAL SPECIFICATION</b>		
Dimensions	Charging Head: 20.5" H x 7.4" W x 7.4" D	
Approximate Weights	Charging Head: 21 lbs.   Pedestal: 12.5 lbs.   Wall mount bracket: 11.5 lbs.	
Mounting Option	Wall or Pedestal mount	
Cable Length	18 ft standard, 25 ft optional	
Cable Management System	Optional	
<b>REGULATION</b>		
Safety	UL 2594 / CSA C22.2 No. 280-16   UL 2231-1 / CSA C22.2 No. 281.1-12, UL 2231-2 / CSA C22.2 No. 281.2-12 certified	
EMI	FCC Part 15 Class A compliant	
Energy Efficiency	Energy Star certified	
Compliance	California Type Evaluation Program (CTEP) certified, Buy American ACT (BAA) compliant	
Accessibility	ADA compliant	