Interactive Flat
Panel Displays
with the Windows
Open Architecture
Controller

D3210BK, D5530BK, D6520BK, D7510BK and D8600BK





NEW IDEAS. NEW SOLUTIONS.

www.electronicofficesystems.com PH: (973) 808-0100 330 Fairfield Road Fairfield, NJ 07004



Life-like HD & 4K resolution display

Multi-touch

Transform Your Business Communications with Ricoh IFPDs

Now more than ever, businesses are adopting visual communications technology to enable faster information sharing and group decision making, innovative learning and brainstorming sessions, and high-definition video conferencing with remote team members to collaborate in real time with reduced costs.

At the heart of every visual communications solution is an Interactive Flat Panel Display (IFPD), a high-resolution touchscreen video monitor. Ricoh – a name you know and trust for document production solutions – offers a complete line of IFPDs in a variety of sizes from 32" to 86" to meet all of your audio/visual communication needs.



The 32" **D3210BK** is optimized for smaller huddle spaces and desktop use. Great for impromptu meetings, this portable model offers HD resolution for sharp, bright images and supports up to 10 simultaneous touch points. Eliminate contention for conference rooms; the versatile D3210BK turns any space into a meeting place. It can be used in horizontal or portrait mode, laid flat on a table, and can even double as a PC monitor on an executive's desk for added value.

The **D5530BK**, **D6520BK** and **D7510BK** offer a choice of 55", 65" or 75" screens to meet a wide range of audience and conference room sizes. These Collaboration Boards deliver life-like image quality with 4K resolution, and realize highly accurate touch response for up to 20 simultaneous touch points using FlatFrog InGlass™ technology for a light, sleek design. Equipped with a motion detection sensor that automatically wakes the system when users approach, these IFPDs are rated for IP5X dust resistance for use in frontline environments like construction sites and factory floors. The D5530BK offers a 90° rotation unit option for use in tight spaces and to display images in portrait orientation.





The **D8600BK** is a 4K resolution IFPD for life-like, life-size presentations and meetings demanding maximum visual impact. This 86" IFPD employs second-generation Shadow Sense touchscreen technology and supports up to 10 simultaneous touch points. Intended for larger, more exclusive environments such as corporate boardrooms, auditoriums, conference centers and broadcast studios, the D8600BK brings the biggest ideas to life.

Unified Platform Approach

Whichever IFPD is the right size for your needs, Ricoh has a model to fit any room and budget while offering an identical user experience. Our *unified platform approach* means once you've learned how to operate one Ricoh IFPD, you've learned how to use them all. Every Ricoh IFPD can be mounted on a rolling stand or attached to a wall. All use a passive touch pen or finger for simplified ease of use. All offer a wide range of video interface ports to display images from virtually any source. And when equipped with the proper licenses and accessories, every Ricoh IFPD can perform every function. So whether your application calls for a stand-alone video display, interactive touchscreen capabilities, document creation and annotation, or real-time remote collaboration and video conferencing, the only difference is the size of the display.

Open Architecture Controllers Open a World of Possibilities

If the IFPD is the heart of every visual communications solution, then the controller is its brain.

A controller enables capabilities beyond simple video display. Basic whiteboarding and computer desktop display functions can be performed using a PC as an external controller. Touchscreen capabilities are supported through a secondary USB connection.

To take full advantage of the entire spectrum of IFPD capabilities, Ricoh offers a choice of two powerful Windows 10-based controllers. Both transform the IFPD into a super-sized high definition PC with touchscreen capabilities. Their open architecture means you can install and run virtually any Windows 10-compliant software application you need, in addition to accessing their secured whiteboarding, remote collaboration and video conferencing capabilities (with the proper accessories and site licenses). Surf the web, access cloud services, and run Windows 10 software apps on a digital canvas as big as your ideas.





The **Ricoh Windows 10 i5 Controller** is the standard version best for users running office-type Windows 10 applications with visual communications needs. The **Ricoh Windows 10 i7 Controller** is the premier version recommended for more processor-intensive applications such as video rendering, 3D modeling and high-end large-scale graphic display in addition to handling your visual communications requirements. Both seamlessly install into the Open Pluggable Specification (OPS) slot on the side of every Ricoh IFPD for a completely embedded UC solution with touchscreen simplicity.

Engaging Meetings, Lectures and Brainstorming Sessions

Make presentations and classroom exercises come alive. Ricoh open architecture controllers ship with our IWB Lt drawing and document annotation software preloaded. Ricoh also supports a growing library of native and third party software applications certified for use with these controllers including whiteboarding solutions, project management and collaboration software, IFPD application organization, and others. Ricoh even offers an Education version of the Windows 10 i5 Controller bundled with interactive software for the classroom. Or, install a Windows 10-compliant whiteboarding, project management or educational software app of your liking.



Improve Teamwork with Remote Collaboration and Video Conferencing



Connect globally. Up to 20 Ricoh IFPDs can be installed on the same network. When a Remote License Type 1 is purchased for each site, remote team meetings with data sharing and simultaneous document viewing and markup at each endpoint is enabled. Add a camera/microphone unit and a subscription to Ricoh's optional video conferencing solution, called the Unified Communications System Advanced (UCSA) service, for real-time, face-to-face video conferencing with up to 100 participants per call. Already have a video conferencing service? Our open architecture controllers give you the freedom to use Skype® for Business, Zoom®, Microsoft Teams™ or most any cloud-based solution of your choosing. Run MS Office 365™ apps, browse the internet, and share documents, videos and data with remote team members. Accomplish in minutes what used to take hours or days while eliminating unnecessary in-person meeting and travel expenses.

Let Ricoh help you collaborate more efficiently wherever your employees are located. Our extensive national support network is the perfect match for all of your visual communications needs.

D3210BK / D5530BK / D6520BK / D7510BK / D8600BK SYSTEM SPECIFICATIONS

| Model | D3210BK | D5530BK | D652 | 20BK | D7510BK | | D8600BK | |
|------------------------------------|---|--|----------------------------|---|--|--|---|--|
| IFPD Screen Specifications | 552 105K | Dobbook | 3001 | | Distribution | | Doodolk | |
| Diagonal Screen Size | 31.5" (28.3" H x 16.3" V) | 55" (47.6" H x 26.8" V) | 65" (56.2" H | 1 x 31 6" V) | 75" (64.9" H x 36.5" | V) | 86" (74.6" H x 41.9" V) | |
| Display Type | 5115 (E015 11 X 1015 1) | 33 (17.6 17.7 26.6 17 | Liquid Crystal | | 75 (01.5 11 × 50.5 | • , | 00 (/ 110 11 / 1115 0/ | |
| Orientation | Horizontal, Vertical, Flat | Horizontal, Vertical | Liquiu ciystai | 2.5p.ay (202) | Horizontal | | | |
| Backlight | LED system | Tronzontal, vertical | DLED 9 | system | Homzonia | | LED system | |
| Resolution | 1,920 x 1,080 dpi (HD) | | | | 60 dni (4K) | | | |
| Color | 16.77 million (8 bit color) | 3,840 x 2,160 dpi (4K) 1.07 billion (10 bit color) | | | | | | |
| Brightness | 500 cd/m ² | | 440 c | 0 cd/m ² 410 cd/m ² | | | | |
| Aspect Ratio | 500 ta/ | <u> </u> | 16 | | | | 110 ca, | |
| Contrast Ratio | 3,000:1 | 4,000:1 | 5,00 | | 4,000:1 | | 1,200:1 | |
| Pixel Pitch | 0.364 x 0.364 mm | 0.315 x 0.315 mm | 0.372 x 0 | | 0.429 x 0.429 mm | 1 | 0.4935 x 0.4935 mm | |
| Response Speed | < 10 milliseconds | | | < 8 milliseconds | | | | |
| Viewing Angle (H/V) | | Left and Right: 178° / Up and Down: 178° | | | | | | |
| Display Glass | | | nti-glare glass | | 4 mm thick anti-glare glass | | | |
| Speakers | 8 W x 2 - bottom | 12 W x 2 - bottom | | 12 W x 2 - front | | | 12 W x 2 - bottom | |
| Motion Detection Sensor | Not Supported | | Stan | | | | Not Supported | |
| Touch Sensor Specifications | | | | | | | | |
| Technology | PCAP (Capacitive Touch) | InG | ilass™ by FlatFro | g + Optical Bond | ing | | 2 nd Gen. Shadow Sense | |
| Maximum Touch Points | 10 (4 w/IWB software) | | 20 (4 w/IWI | (B software) | | | 10 (4 w/IWB software) | |
| Touch Screen Interface | | | USB 3.0 | Type B | | | | |
| Positional Accuracy | +/- 2 mm (over 90% area) | | 1 n | mm +/- 2 mm (over 90% area) | | | | |
| Operating Systems | | Multi-touch: Windows 7, 8.1, | 10, Single-touc | uch: Windows 7, 8.1, 10 & Mac OS X 10.8 - 10.15 | | | | |
| Connectivity Specifications | | | | | | | | |
| Video Input | | Mini D-Sub 15-pin (VGA) x 1 HDMI x 1 (HDCP compliant) DisplayPort x 1 (HDCP compliant) DisplayPort x 1 (HDCP compliant) | | | | fini D-Sub 15-pin (VGA) x 1 IDMI x 1 (HDCP compliant) DayPort x 1 (HDCP compliant) DVI-D x 1 (HDCP compliant) | | |
| Video Output | | | DisplayPort x 1 (I | HDCP compliant) | | | | |
| Audio Input | | 3.5 m | m Line In x 1 (fo | r use with VGA i | nput) | | | |
| Audio Output | +/- Speaker Terminals x 1 | 3.5 mm Headphone Out x 1 +/- Speaker Terminals x | | | | | +/- Speaker Terminals x 1 | |
| USB Device Interfaces | USB 3.0 Type A x 4 (Self-powered 7.5 W) (rear) | USB 3.0 Type A x 6 (2 rear, 4 side) | | | | USB 2.0 Type A x 4 USB 3.0 Type A x 4 (side) | | |
| Control & Management | RS-232C x 1 (Input) / RS-232C x 1 (Output) | | | | | | | |
| OPS Slots | 2 - Controller Module x 1 / Capture Module x 1 | | | | | | | |
| Remote Sharing | Up to 20 interactive displays and projector systems. Plus up to 20 remote devices (iOS®, Android® and Windows®) per IFPD* | | | | | | | |
| Remote PC Operation | Supported using USB 3.0 Type B and Video Input connections | | | | | | | |
| General Specifications | | | | | | | | |
| Dimensions (WxDxH) | 31.0" x 2.75" x 18.9" (789 x 70 x 480 mm) | 50.8" x 3.0" x 30.4" (1,290 x 78 x 773 mm) | 59.4" x 3.3 (1,508 x 83 | | 68.2" x 3.1" x 41.1 (1,733 x 79 x 1,045 n | | 79.1" x 4.9" x 47.25" (2,009 x 125 x 1,200 mm) | |
| Weight | 37.5 lbs. (17 Kg) | 81.5 lbs. (37 Kg) | 103.6 lbs | i. (47 Kg) | 134.5 lbs. (61 Kg) | 1 | 269 lbs. (122 Kg) | |
| Power Source | | | AC 100 – 240 | | | | | |
| Power Consumption | < 215 W / < 0.3 W | < 255 W / < 0.5 W | < 380 W | | < 0.5 W < 500 W / < 0.5 W < 510 W / < 0.5W | | | |
| Standard Accessories | | Wirele | ess Remote Contr | rol, Touch Pen & Eraser | | | | |
| IP5X Dust Resistant | Not Certified | Certified Not Certified Not Certified | | | | | | |
| Advanced Display Features | Aspect, Adjust Screen, Touch Fea | S232C Control Daisy Chain, Picture Mode (including Low Blue Light mode), Backlight, Contrast, Brightness, Sharpness, Color Temperature, Picture-in-Picture, Picture-by-Picture Aspect, Adjust Screen, Touch Feature, Language, Power Save, Control Setting, Touch Control Setting, Set Monitor ID, DICOM Simulation (D5530BK, D6520BK, D7510BK only), Motion Detection Sensor (D5530BK, D6520BK, D7510BK only), Advanced Information, Sound Mode, Treble, Bass, Balance, Volume, Mute, Speaker, Audio Source | | | | | | |
| Options & Accessories | | | | | | | | |
| Stands | Type 1 | Type 6 BK + Rotation Unit | | Туре | 7 BK | | Type 4 BK | |
| Camera/Microphone | | Logitech Recommended: Rally | 4K Cam, MeetU | p 4K Cam, Conne | ect HD Cam or C930e HD | Cam | | |
| Spare Pen/Eraser | Touch Pen Type 2 BK | | | SDW | /-KIT | | | |
| Windows 10 Open Architect | ure Controller Specifications | | | | | | | |
| Version | Win | dows 10 i5 Controller | | | Windows 10 | i7 Contr | oller | |
| Type / Installation | 1 | 1-piece Controller Module. Install into upper Open Pluggable Specification (OPS) Slot on side of IFPD: | | | |)s | | |
| CPU | Intel Core i5 6500TE C | Intel Core i7 8700TE CPU @ 2.4 GHz (Base) / 3.4 GHz (Turbo) | | | | | | |
| Internal Storage/Memory | 500 GB Hard Disk Drive (HDD) / 16 GB RAM 512 GB Solid State Drive (SSD) / 16 GB RAM | | | | | | | |
| Operating System | Windows 10 Professional - 64 bit | | | | | | | |
| Installed Software | Ricoh IWB Lt Software, Ricoh UCS Advanced (My Meeting Video), Customer can install Windows 10-compliant applications | | | | | | | |
| Network Interfaces | Wired: 10/100/1000B | Wired: 10/100/1000Base-T (RJ-45) x 1 & Wireless: IEEE 802.11 ac/a/b/g/n x 1 for management, remote collaboration and video conferencing*. Plus additional audio and video input/output jacks. | | | | | | |
| Item | | EDB Codo | Item | | | | FDP Code | |

| Item | EDP Code | Item | EDP Code |
|--------------------------------------|----------|---|-----------------|
| Ricoh Interactive Whiteboard D3210BK | 432424 | IWB Desktop Stand Type 1 (for D3210BK) | 755213 |
| Ricoh Collaboration Board D5530BK | 432523 | Ricoh Collaboration Board Stand Type 6 BK for D5530BK (2 boxes) | 432534 & 432535 |
| Ricoh Collaboration Board D6520BK | 432526 | Ricoh Collaboration Board Rotation Unit Type 1 (for Stand Type 6 BK) | 432542 |
| Ricoh Collaboration Board D7510BK | 432545 | Ricoh Collaboration Board Stand Type 7 BK for D6520BK & D7510 (2 boxes) | 432530 & 432531 |
| Ricoh Interactive Whiteboard D8600BK | 432447 | Ricoh Collaboration Board Stand Type 4 BK for D8600BK (2 boxes) | 432451 & 432452 |
| Windows 10 i5 Controller | 432308 | Touch Pen Type 2 (for D3210BK only) | 755219 |
| Windows 10 i7 Controller | 432563 | Touch Pen and Eraser Kit (55"- 86") | SDW-KIT |
| Ricoh IWB Remote License Type 1 | 431128 | Logitech Wireless Keyboard/Touchpad | 920-008357 |

Disclaimer: Brightness will depend on input mode and other picture settings. Brightness level will decrease over time. USB with security or anti-virus software installed are not compatible. Remote sharing function requires Remote License. Remote License is required for collaborative meetings. For wall mounting, use a standard VESA mount (not supplied by Ricoh). Via intranet, required line speed: Min. 200Kbps, recommended over 512Kbps. For availability of models, options and software, please consult your local Ricoh supplier. "When using licensed IWB Lt software.



www.ricoh-usa.com

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-800-63-RICOH
@2020. Ricoh USA, Inc. All rights reserved. Ricoh and the Ricoh logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of
their respective owners. The content of this document, and the appearance, features and specifications of Ricoh products and services are subject to change from
time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no
representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions
in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only
warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

