

TELLUS POWER GREEN DC FAST CHARGER

60 kW Charging Station



**Model :
TP-EVPD-60kW**

- ✓ Powerful Compact All-In-One DC Charger
- ✓ Simple Air-Cooled Power Modules
- ✓ Easy to Maintain
- ✓ Parallel Charging Feature
- ✓ Output Voltage of 1000VDC
- ✓ OCPP 1.6J
- ✓ Credit Card Reader
- ✓ Cord Management



NEW IDEAS. NEW SOLUTIONS.
www.electronicofficesystems.com PH: (973) 808-0100
330 Fairfield Road Fairfield, NJ 07004

TELLUS POWER GREEN DC FAST CHARGER

60 kW Charging Station



**Model :
TP-EVPD-60kW**



Product #	TP5-60-480-2
Model #	TP-EVPD-60KW
Input	480VAC (3P+N+PE) 60Hz
Output Voltage	200 - 1000VDC
Output current	Upto 150A
FLA Breaker Rating	80A 100A
Connectors	Dual CCS1
Cyclic Charge Mode	60kW
Parallel Charge Mode	30 kW per Port
Efficiency	≥94% at nominal output power
Power factor	> 0.98
Display	10" touch screen
Access Control	RFID : ISO/IEC 14443A/B Credit Card Reader (Optional)
Metering	DC kWh meter per each connector
Operating temperature	-22°F to 131°F (-30°C to 55°C)
Altitude	6500' (2000m)
Working Storage Humidity	≤ 95% RH ≤ 99% RH (Non-condensing)
Dimensions (L x D x H)	29" x 19" x 72"
Protective Class	NEMA 3S (IP54), IK10
Cooling system	Air cooling fans
Weight	617 lbs (280kgs)
DC Charge System	Mode 4 - IEC-61851, ISO-15118, DIN 70121 Mode 4 - CHAdeMO 0.9, 1.0
Charging cable	16ft (5m), Cable Retractor Included
Communication Protocol	Ethernet, 4G/WiFi OCPP 1.6J
Electrical Safety: GFCI	RCD 20 mA Type A
Electrical Safety: Surge Protection	20 kA
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground
Electrical Safety: Output Short	Output power disabled when output is short circuited
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics
Emergency Stop	Emergency Stop Button Disables Output Power
Regulatory Compliance	UL-2202 CSA C22.2#107.1:2016 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012